



LINK BOX TECHNICAL DATA SHEET

Drw. No. 17.06.03 Article No. 21003001/0

 Issued Date:
 12.10.2021

 Rev. Date:

 Rev.
 00

Type		3.1	
- Description	Three Phase Earthing Link Box with SVL for Single Cable		
- Designation	Wall Type		
- Bonding		Earthing	
- Sheath Voltage Limiter	qty	3	
- Phase No.		3	
Earth		1	
Drawing Number		17.06.03	
- Article No	2	21003001/0	
Electrical Characteristics			
- Rated Frequency	50/60 Hz		
- SVL Type (*)	Up to 10 kV / Optional		
Protection Class		IP 66	
Material			
- Enclosure	Stainless Steel AISI304 (AISI316 optional)		
- Body Thickness (**)	3 mm		
- Cover Thickness	3 mm		
- Connection Links	10 μm Tinned Electrolytic Copper		
- Connection Links Dimension	50x10 mm (500 mm2)		
- Gasket	Silicone		
- Cable Glands	4x48 mm		
- PD Cable Glands	3x21 mm		
- Cable Glands Insulation	Silicone gasket & EPR tape		
- Insulation	Epoxy Support Insulator		
- Conductor Fixing	Conductor Flexconn - 300-500 mm2		
- Painting Process	Electro Static Polyester Powder Paint		
- Painting Code	RAL 7032		
- Labeling Material	Stainless Steel		
- Protection Cover		PET-G	
AC Impulse Test			
- Phase-to-Phase	60	kV	
- Phase-to-Earth	40	kV	
Voltage Withstand Test			
- AC	20	kV/1 min	
- DC	25	kV/5 min	
Short Circuit Test			
- Symmetrical	N/A		
Internal Power Arcing Test (Symmetrical)	40	kA/0.1 sec	

^{*} In case of mismatch in given values, technical drawing provided along with the Order Confirmation is valid. Ask for conformity if SVL is out of EMELEC's scope.


^{**} Body Thickness might differ related to technical drawing revision. For exact value, refer to technical drawing provided along with the Order Confirmation






LINK BOX TECHNICAL DATA SHEET

Bonding Cable



Schematic Diagram



Enclosure Dimensions (*)

Width	750 mm	
Length	670 mm	
Heigth	390 mm	
Weigth	75 kg	
Filling Compund	l (Optional)	
Volume	N/A	

^{*} Scheme and dimensions are not to be mentioned as final drawing. For exact dimensions, refer to technical drawing provided along with the Order Confirmation

^{**} Given are approximate values. Actual values might sligthly differ.