



LINK BOX TECHNICAL DATA SHEET

Drw. No. 12.06.07 Article No. 15007001/0

 Issued Date:
 12.08.2021

 Rev. Date:

 Rev.
 00

Туре	LB. U . E .3SA . 3 . 1					
- Description	Earthing Link Box with SVL for Single Cable					
- Designation	Underground Earthing qty 3 3					
- Bonding						
- Sheath Voltage Limiter						
- Phase No.						
Earth	1					
Drawing Number	12.06.07					
- Article No	15007001/0					
Electrical Characteristics						
- Rated Frequency	50/60 Hz					
- SVL Type (*)	Up to 10 kV / Optional					
Protection Class	IP 68					
Material						
- Enclosure	Stainless Steel AISI304 (AISI316 optional)					
- Body Thickness (**)	2 mm					
- Cover Thickness	3 mm					
- Connection Links	10 μm Tinned Electrolytic Copper					
- Connection Links Dimension	50x10 mm (500 mm2)					
- Gasket	Silicone					
- Cable Glands	4x48 mm					
- Cable Glands Insulation	Silicone gasket & EPR tape & Mastic Tape & Heat Shirinkable Tube					
- Insulation	Epoxy Support Insulator					
- Conductor Fixing	Conductor Flexconn - 400-500 mm2					
- Painting Process	Electro Static Polyester Powder Paint					
- Painting Code	RAL 7032					
- Labeling Material	Stainless Steel					
- Protection Cover	PET-G					
AC Impulse Test						
- Phase-to-Phase						
- Phase-to-Earth	40 kV					
Voltage Withstand Test						
- AC	20 kV/1 min					
- DC	25 kV/5 min					
Short Circuit Test						
- Symmetrical	N/A					
Internal Power Arcing Test (Symmetrical)	40 kA/0.1 sec					
Internal Power Arcing Test (Symmetrical)	40					


^{*} In case of mismatch in given values, technical drawing provided along with the Order Confirmation is valid. Ask for conformity if SVL is out of EMELEC's scope.

^{**} Body Thickness might differ related to technical drawing revision. For exact value, refer to technical drawing provided along with the Order Confirmation

Bonding Cable

- Туре									
	d Dia		4		В	(C	I	D
Cross-Section	Inner		max (mm)	min	max	min (mm)	max (mm)	min (mm)	max (mm)
300-500	44	20	28	22	40	N/A	N/A	N/A	N/A
60									

Schematic Diagram



- LINK BOX
 EARTHING BUS BAR
 CABLE END FIXING PIECES
 DISCONNECTABLE SURGE ARRESTERS
 BONDING CABLE
- 6 EARTHING CABLE

Enclosure Dimensions (*)

Width	690 mm	
Length	670 mm	
Heigth	334 mm	
Weigth	77 kg	
Filling Compund (C	Optional)	
Volume	47 lt (**)	

^{*} Scheme and dimensions are not to be mentioned as final drawing. For exact dimensions, refer to technical drawing provided along with the Order Confirmation

^{**} Given are approximate values. Actual values might sligthly differ.