



LINK BOX TECHNICAL DATA SHEET

Drw. No. 19.04.04 Article No. 23204001/0

 Issued Date:
 4.08.2021

 Rev. Date:

 Rev.
 00

Type - Description	LB. MV . SB .6SA					
- Description - Designation	Wedutin Voltage - Both Ends S. Point Bortaing Link Box for Single Under					
- Bonding						
- Sheath Voltage Limiter	Single Point aty 6					
- Phase No.	qty					
Earth						
Drawing Number	15	9.04.04				
- Article No		4001/0				
Electrical Characteristics						
- Rated Frequency	50/60	Hz				
- SVL Type (*)	Up to 6 kV / O	ptional				
Protection Class	II	P 68				
Material						
- Enclosure	Stainless Steel AISI304 (AISI316 op	otional				
- Body Thickness (**)		2 mm				
- Cover Thickness		2 mm				
- Connection Links	10 μm Tinned Electrolytic (Coppe				
- Connection Links Dimension	30x3 (90	mm2				
- Gasket		Silicone				
- Cable Glands	7x	21 mm				
- Cable Glands Insulation	Silicone gasket & EPR tape & Mastic Tape & Heat Shirinkable	e Tube				
- Insulation	Epoxy Support In	sulato				
- Conductor Fixing	Cable Lug - Max. 50	0 mm2				
- Painting Process	Electro Static Polyester Powde	r Pain				
- Painting Code	RA	L 7032				
- Labeling Material	Stainles	s Stee				
- Protection Cover		N/A				
AC Impulse Test						
- Phase-to-Phase	35	k۷				
- Phase-to-Earth	17,5	k۷				
/oltage Withstand Test						
- AC		//1 mir				
- DC	15 kV	//5 mir				
Short Circuit Test						
- Symmetrical	N/A					
Internal Power Aroing Toot (Symmetrical)	40 LN/	1 00-				
Internal Power Arcing Test (Symmetrical)	10 kA/0).1 se				

^{*} In case of mismatch in given values, technical drawing provided along with the Order Confirmation is valid. Ask for conformity if SVL is out of EMELEC's scope.


^{**} Body Thickness might differ related to technical drawing revision. For exact value, refer to technical drawing provided along with the Order Confirmation

Bonding Cable

- Type											Single
	Gland	d Dia	,	4	I	В	(C	I	כ	
Cross-Section	Outer	Inner	min	max	min	max	min	max	min	max	
(mm2)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
Max 50 mm2	21	17		11	8	15	N/A	N/A	N/A	N/A	



Schematic Diagram



- (1) LINK BOX
- (2) EARTHING BUS BAR
- DISCONNECTABLE LINKS
- DISCONNECTABLE S.A.
- BONDING CABLE
- (6) EARTHING CABLE

Enclosure Dimensions (*)

Width	450 mm	
Length	380 mm	
Heigth	210 mm	
Weigth	20 kg	
Filling Compund	(Optional)	
Volume	N/A	

Scheme and dimensions are not to be mentioned as final drawing. For exact dimensions, refer to technical drawing provided along with the Order Confirmation
 Given are approximate values. Actual values might sligthly differ.